



ScandMist 200P OEM Oil fume & VOC filtration

| General | Product | Units | ScandMist 200P OEM |
|---------------------|------------------------------------|-------|--------------------------------------|
| | Application | | Rubber & plastic fumes |
| | Capacity (nominal) | m³/h | 2000 |
| | Part number | | C1B20PB100000A |
| Connections | Inlet type | | Jacobs |
| | Inlet diameter | mm | 200 |
| | Drain | | 2 off, 2" Threaded (BS 21) Female |
| | Air inlet options | | Left/Right/Back |
| | Exhaust | | On top |
| Filters | Filters/stage | | |
| | Stage 1 filter (coalescer) | | 97090M0599 |
| | Stage 2 filter (HEPA H13) | | 800530024917 |
| | Stage 3 filter (Carboactiv Cube N) | | 800656024342 |
| | Available external pressure drop | Pa | 200 |
| Motor | Туре | | Electrically commutated |
| | Part number | | 9709005278 |
| | Quantity | | |
| | Mains supply | | 3 ~ 380-480 V, 50/60 Hz |
| | Ventilation | | TEFC |
| | Power | kW | 3,7 |
| | Maximum current | А | 4,6 |
| | Speed | RPM | Max 4100 |
| | Environmental protection | | IP54 |
| Physical properties | Width | mm | 1416 |
| | Height | mm | 971 (excluding inlet transition) |
| | Depth | mm | 685 (excluding inlet transition) |
| | Weight | kg | Clean filters: 233, Wet filters: 288 |
| | Noise level | dB(A) | <69 |
| | Fan | | Backward bent blades |
| | Finish | | Powder coating inside and outside |
| Controls | Control system | | Micaflex MF-PFA |
| | Differential pressure gauges | | 3 of |
| Options | Oil pump | | N/A |
| | Level sensor | | 9908900187 |
| | Prefilter demister | | Included |
| | Spray | | Not included |
| | Silencer | | Insulated fan housing |


EC fan and motor

The standard EC fan and motor delivers good energy efficiency with quiet operation.



Connecting interface

Wiring via a Harting male/female connector. Quick and easy installation with all connecting interfaces at one spot.



Fan pressure

Power

| Powe | Power | | |
|------|-------|--|--|
| 1 | L1 | | |
| 2 | L2 | | |
| 3 | L3 | | |
| 4 | Ν | | |
| 5 | PE | | |
| | | | |

| Signal exchange | | | | |
|-----------------|--------------------------------|--|--|--|
| 1 | ON/OFF (make contact) | Input: ON/OFF | | |
| 2 | М | | | |
| 3 | Output Signal: In Operation | Output: In Operation | | |
| 4 | М | | | |
| 5 | AL1 | Al 1 M- h/D | | |
| 6 | М | Alarm 1, Motor/Power | | |
| 7 | AL2 | Alarm 2, System pressure high/low/operation signal | | |
| 8 | N | | | |
| 9 | AL3 | Alarm 3, System pressure high/low/operation signal | | |
| 10 | N | | | |
| 11 | Reset | Reset for alarms | | |
| 12 | N | | | |
| 13 | Al2 | Analog output 2 of Micaflex MF-PFA | | |
| 14 | N | | | |

