

Airpocket Select Power

Product Range



Features



Applications



Filter Class

G

M

Coarse



KEY FACTS

- Synthetic filter media
- Long service life
- High dust holding capacity
- Suitable for air flows up to 4250 m³/h
- Low Pressure drop

DESIGN

Progressively-structured, polyester media. Conically sewn into single pockets and fitted into a robust plastic frame with integrated air guides.

APPLICATIONS

Prefiltration for gas turbine air intakes.

Airpocket Select Power

PERFORMANCE DATA

Article No.	ISO 16890	Filter Class	Dimensions	Pockets	Flow Rate	Pressure Drop
		EN 779	mm		m ³ /h	Pa
800321024387	Coarse 70%	G4	592 x 592 x 200	6	3400	40
800321024383	Coarse 70%	G4	592 x 592 x 300	6	3400	38
800321024384	Coarse 70%	G4	592 x 592 x 360	6	3400	35
800321024385	Coarse 70%	G4	592 x 592 x 500	6	3400	33
800321024386	Coarse 70%	G4	592 x 592 x 600	6	3400	30
800321024387	Coarse 80%	M5	592 x 592 x 200	6	3400	65
800321024388	Coarse 80%	M5	592 x 592 x 300	6	3400	62
800321024389	Coarse 80%	M5	592 x 592 x 360	6	3400	60
800321024390	Coarse 80%	M5	592 x 592 x 500	6	3400	55
800321024391	Coarse 80%	M5	592 x 592 x 600	6	3400	50

SPECIFICATION

Recommended air velocity	2.5 m/s ± 20 %	Recommended final pressure drop	250 Pa
Heat resistance	Max. 80 °C	Moisture resistance	100 % rel. humidity
Regenerable	No	Incinerable	Yes

OPTIONS

Gasket	EPDM flat gasket, 1 or 2 sides
Header depth	25 mm or 20 mm
Frame	Plastic or metal